

SafeStat Online

October 07, 2008 SafeStat Release
 Contains data as of September 26, 2008
 Updated Monthly



Overview | Accident | Driver | Vehicle | Safety | History

US DOT #: 1475224 MC #: 559789 Carrier Name: LUIS ORTEGA Carrier Operation: INTERSTATE


Carrier Information

[How do I correct my data?](#) [Print Ready Version](#) [Help](#)

The October 07, 2008 SafeStat Release contains **Carrier Information** as of September 26, 2008, which is the date of the latest SafeStat run. For more up-to-date **Carrier Information** visit the SAFER [website](#).

Carrier Name	LUIS ORTEGA		DBA	ORVI TRUCKING
Address	5208 LA JOLLA LANE DALLAS, TX 75236		Mailing Address	5208 LA JOLLA LANE DALLAS, TX 75236
Telephone/Fax	(972) 780-8426/(972) 780-8426		Email	ORVI@SBCGLOBAL.NET
Number of Power Units	4	Number of Drivers	4	Transports HM
Date of Last MCS-150 Update	01/10/2007		Date of Last FMCSA Review	Review Type

SafeStat Information



Performance vs. Available Data

Performance Groups	Data Groups
[1] Extensive	[1] Extensive
[2] Moderate	[2] Moderate
[3] Minimal	[3] Minimal
[1] All SEAs less than 50	
[2] No Deficient SEAs (All Below 75)	
[3] 1 Deficient SEA (One Above 75)	
[4] 2+ Deficient SEAs (SafeStat Score)	

* Specific SafeStat information has been temporarily removed.

SafeStat

Score	
Category	
State Rank	
National Rank	

* Specific SafeStat information has been temporarily removed.

Link to [Click to view ISS-D Recommendation](#) ISS-D (Inspection Selection System) recommendation information

* Specific SafeStat information has been temporarily removed, [click here](#) for details.

SafeStat Calculation

$$\text{SafeStat Score} = 2 \times \text{Accident SEA Value} + 1.5 \times \text{Driver SEA Value} + \text{Vehicle SEA Value} + \text{Safety Management SEA Value}$$

*	*	0	68.17	Insuf. Data
---	---	---	-------	-------------

* Specific SafeStat information has been temporarily removed, [click here](#) for details.

SafeStat calculates a SafeStat score to rank carriers in descending order by their safety status (i.e. a carrier with the highest SafeStat score is the first ranked carrier in terms of poor safety status). SafeStat does not assign SafeStat scores to all carriers. To obtain a SafeStat Score, a carrier must be deficient in at least **two different Safety Evaluation Areas (SEAs)**. SEA values range from 0 (best) to 100 (worst). A SEA with a value from 75 to 100 is defined as deficient (highlighted in **BOLD** type). SEA Values that are less than 75 are not used in the calculation of a SafeStat Score.

CAUTION: Please verify [important data](#) before relying on SafeStat results. Inaccurate or out-of-date normalizing data can result in SafeStat results that do not accurately reflect the motor carrier's safety status.

