

SafeStat Online

October 07, 2008 SafeStat Release
 Contains data as of September 26, 2008
 Updated Monthly

List Search

Overview | Accident | Driver | Vehicle | Safety | History

US DOT #: 270715 MC #: 170722 Carrier Name: AMERICAN INTERNATIONAL MOVERS ... Carrier Operation: INTERSTATE


Carrier Information

[How do I correct my data?](#) [Print Ready Version](#) [Help](#)

The October 07, 2008 SafeStat Release contains **Carrier Information** as of September 26, 2008, which is the date of the latest SafeStat run. For more up-to-date **Carrier Information** visit the SAFER [website](#).

Carrier Name	AMERICAN INTERNATIONAL MOVERS INC		DBA	
Address	816 HWY 41 SOUTH FORSYTH, GA 31029		Mailing Address	816 HWY 41 SOUTH FORSYTH, GA 31029
Telephone/Fax	(478) 994-1324/(478) 994-2544		Email	gplus12@aimovers.com
Number of Power Units	98	Number of Drivers	90	Transports HM
Date of Last MCS-150 Update	04/03/2008		Date of Last FMCSA Review	10/25/2006
			Review Type	COMPLIANCE REVIEW

SafeStat Information



Performance vs. Available Data

Performance Groups	Data Groups
[1] All SEAs less than 50	[1] Extensive [2] Moderate [3] Minimal
[2] No Deficient SEAs (All Below 75)	
[3] 1 Deficient SEA (One Above 75)	
[4] 2+ Deficient SEAs (SafeStat Score)	

* Specific SafeStat information has been temporarily removed.

SafeStat

Score	
Category	* Specific SafeStat information has been temporarily removed.
State Rank	
National Rank	

Link to [Click to view ISS-D Recommendation](#) ISS-D (Inspection Selection System) recommendation information

* Specific SafeStat information has been temporarily removed, [click here](#) for details.

SafeStat Calculation

$$\text{SafeStat Score} = 2 \times \text{Accident SEA Value} + 1.5 \times \text{Driver SEA Value} + \text{Vehicle SEA Value} + \text{Safety Management SEA Value}$$

*	*	56.29	50.89	Insuf. Data
---	---	-------	-------	-------------

* Specific SafeStat information has been temporarily removed, [click here](#) for details.

SafeStat calculates a SafeStat score to rank carriers in descending order by their safety status (i.e. a carrier with the highest SafeStat score is the first ranked carrier in terms of poor safety status). SafeStat does not assign SafeStat scores to all carriers. To obtain a SafeStat Score, a carrier must be deficient in at least **two different Safety Evaluation Areas (SEAs)**. SEA values range from 0 (best) to 100 (worst). A SEA with a value from 75 to 100 is defined as deficient (highlighted in **BOLD** type). SEA Values that are less than 75 are not used in the calculation of a SafeStat Score.

CAUTION: Please verify [important data](#) before relying on SafeStat results. Inaccurate or out-of-date normalizing data can result in SafeStat results that do not accurately reflect the motor carrier's safety status.

