

SafeStat Online

November 04, 2008 SafeStat Release
 Contains data as of October 24, 2008
 Updated Monthly

List Search

Overview | Accident | Driver | Vehicle | Safety | History


US DOT #: 761298 MC #: 343667 Carrier Name: COLONIAL MOVING & STORAGE INC Carrier Operation: INTERSTATE

Carrier Information [How do I correct my data?](#) [Print Ready Version](#) [Help](#)

The November 04, 2008 SafeStat Release contains **Carrier Information** as of October 24, 2008, which is the date of the latest SafeStat run. For more up-to-date **Carrier Information** visit the SAFER [website](#).

Carrier Name	COLONIAL MOVING & STORAGE INC	DBA	
Address	9 VOSE FARM RD STE 270 PETERBOROUGH, NH 03458	Mailing Address	P.O. BOX 434 PETERBOROUGH, NH 03458
Telephone/Fax	(603) 924-5751/(603) 924-5046	Email	colonialmoving@yahoo.com
Number of Power Units	2	Number of Drivers	5
		Transports HM	No
Date of Last MCS-150 Update	08/11/2005	Date of Last FMCSA Review	Review Type

SafeStat Information



Performance vs. Available Data

Performance Groups	Data Groups
[1] All SEAs less than 50	[1] Extensive [2] Moderate [3] Minimal
[2] No Deficient SEAs (All Below 75)	
[3] 1 Deficient SEA (One Above 75)	
[4] 2+ Deficient SEAs (SafeStat Score)	

* Specific SafeStat information has been temporarily removed.

SafeStat

Score	
Category	* Specific SafeStat information has been temporarily removed.
State Rank	
National Rank	

Link to [Click to view ISS-D Recommendation](#) ISS-D (Inspection Selection System) recommendation information

* Specific SafeStat information has been temporarily removed, [click here](#) for details.

SafeStat Calculation

$$\text{SafeStat Score} = 2 \times \text{Accident SEA Value} + 1.5 \times \text{Driver SEA Value} + \text{Vehicle SEA Value} + \text{Safety Management SEA Value}$$

*	*	Insuf. Data	Insuf. Data	Insuf. Data
---	---	-------------	-------------	-------------

* Specific SafeStat information has been temporarily removed, [click here](#) for details.

SafeStat calculates a SafeStat score to rank carriers in descending order by their safety status (i.e. a carrier with the highest SafeStat score is the first ranked carrier in terms of poor safety status). SafeStat does not assign SafeStat scores to all carriers. To obtain a SafeStat Score, a carrier must be deficient in at least **two different Safety Evaluation Areas (SEAs)**. SEA values range from 0 (best) to 100 (worst). A SEA with a value from 75 to 100 is defined as deficient (highlighted in **BOLD** type). SEA Values that are less than 75 are not used in the calculation of a SafeStat Score.

CAUTION: Please verify [important data](#) before relying on SafeStat results. Inaccurate or out-of-date normalizing data can result in SafeStat results that do not accurately reflect the motor carrier's safety status.

